

HY SERIES (SINGLE OUTPUT)



HY1502D/HY1503D
HY1505D/HY1802D/HY1803D

Features: HY1502D/HY1503D/HY1505D/HY1802D/HY1803D

- 2 LCD display current and voltage simultaneously
- Constant voltage and constant current
- Compact size



HY3001/HY2402

Features: HY3001 / HY2402

- 2 LED display current and voltage simultaneously
- Constant voltage and constant current
- Compact size

General Technical Data

Mains voltage: 110/ 220VAC +/-10%, selectable
 Voltage display accuracy: LCD or LED: 1.0%+2digits
 Current display accuracy: LCD or LED: 2.0%+2digits
 Line regulation: CC<0.2%+1mA
 Source effect: CV<0.01%+1mV

Load Regulation: CC<0.2%+3mA
 Load effects: CV<0.01%+3mV
 Ripple & Noise: CV<1mVrms CC<3mArms

Specifications

Model	Output Voltage	Output Current	Display
HY1502D	0 - 15V	0 - 2A	LCD
HY1503D	0 - 15V	0 - 3A	LCD
HY1505D	0 - 15V	0 - 5A	LCD
HY1802D	0 - 18V	0 - 2A	LCD
HY1803D	0 - 18V	0 - 3A	LCD
HY3001	0 - 30V	0 - 1A	LED
HY2402	0 - 24V	0 - 2A	LED